



## VT4000

### 4-CHL FULL HD 1080P MOBILE DVR

The **VT4000** is a 4-channel, 1080p full HD mobile digital video recorder that provides excellent footage and clear picture quality. It has an integrated industry-leading cellular modem. Recorder includes an external panic button to trigger an emergency event.

<b>FULL HD</b> 1920x1080 RESOLUTION	<b>4</b> CHL	ENCRYPTED	CONNECTED
BUILT-IN G-SHOCK SENSOR	ANTI-VIBRATION	IoT	LOCKABLE CASE



VT-PANIC External Panic button

## Key Features:

- Supports 3-channels AHD + 1 analogue channel
- VisionTrack IoT platform for event video
- API available for direct integration into third-party telematics platforms
- GPS/GLONASS receiver
- Highly sensitive positioning solution for live vehicle tracking and reporting
- 90(L) x 28(H) x 120(W)mm (Metal cover size : 125 x 147.5 x 36mm)



# Specifications\*:

<b>Size(mm)</b>		System size(mm) : 90x120x28 (Metal cover size : 125x147.5x36)
<b>Weight(g)</b>		166.5g(System) / 48g(SW KIT) / 427g(Metal Cover-Include Key)
<b>Camera</b>	Resolution	(1) FHD(1920x1080) x 2 Channel : Max Total 30 fps (2) HD x 3 channels(total 45 fps) + D1 x 1 channel(30 fps) (3) D1(720x480, 720x576) x 4 Channel : : Max Total 120 fps
<b>Storage</b>	SD Card	SDHC/SDXC, 1 Slot
<b>Sensor</b>	G-sensor	3 Axis(X,Y,Z), output rate: 100 Hz, Measurement range: -4G ~ +4G Sensitivity : 512LSB/g Zero-g offset : ±70mg
	Gyro	3 Axis(X,Y,Z), output rate: 100 Hz, Measurement range : ±125°/s Sensitivity : 262.4LSB/°/s
<b>Positioning</b>	GNSS	Support GPS/Glonass/QZSS satellite, Data output rate: 1Hz CEP: 2.5m, Accuracy of Velocity: 0.1m/s TTFF: within 1 min after boot
<b>Audio/Video</b>	Buzzer	1
	MIC	1 (External/Internal)
	Audio/Video Out	HP out / CVBS
<b>User interface</b>	LED	3 : Warning LED(Red), Record LED(Blue), Communication LED(Green)
	Button	3 : Panic Button, M1 Button, M2 Button
<b>Communication</b>	3G/4G	Built-in 3G/4G module (External Antenna)
	Wi-Fi / Bluetooth	Support USB Dongle Type
<b>Power</b>	Power spec	DC 12V/24V
<b>Environment</b>	Operating temperature	-10 °C ~ +55 °C
	Storage temperature	-20°C ~ +70 °C
<b>OS</b>		Embedded Linux
<b>Video Codec</b>		H.265+, JPEG
<b>Audio Codec</b>		PCM
<b>Interface</b>		"SD card slot x 1 A/V out x 1 External MIC In x 1 USB slot x 2 (USB 2.0 OTG: Type A, USB 2.0 Host) Serial x 2 (OBDII, GNSS) Video In x 4 (Extension cable) Switch Kit Signal: Alarm In x 3 / Alarm Out x 2 / RPM / Speed DC-in x 1 (B+, GND, ACC) SIM Slot x 1 (Mini-SIM)"
	<b>Application</b>	Record Mode : Continuous/Event/Dual Record Data : Video, Audio, GPS, G-sensor, Gyro, Driving data Event : G-sensor, Panic, Speed over, Alarm in, Parking, System warning, Car signal Network Service : DMS5 A/V out : Video Live out, Voice guidance Miscellany : "G-sensor calibration, High temperature protection, GPS time sync, DST, Encryption(AES)"
<b>Certification</b>		GCF, CE / E-Mark, FCC