

VT-FORS GOLD RIGID



DVS
DIRECT VISION STANDARD
2020



Warning Signage

VT-FORS GOLD RIGID

Bespoke kit built specifically for rigid vehicle types. This kit covers FORS and DVS requirements.

This kit includes the following:

- | | | |
|---|---|--|
| <p>1. VT5500-G-1TB
5CH MDVR
Includes 1TB Hard-drive</p>  | <p>2. VT-C20-MINI**
Forward-facing Camera</p>  | <p>3. VT-LT ALERT
Left-turn Alert</p>  |
| <p>4. VT-CAN-M8*
Side Scan Interface
(Vehicle 2012 or newer)</p>  | <p>5. VT-WNREVERSINGALARM
White Noise
Reversing Alarm</p>  | <p>6. VT-TIMER CUT OUT
Timer cut-out button</p>  |
| <p>7. VT-M4-7-AHD (Kit)
4CH AHD Monitor
Includes 5M Cable, F2F
Convertor, Brackets</p>  | <p>8. VT408-AHD x2
HD Side-View Camera</p>  | <p>9. VT408 Spacer 50mm x2
VT408 Spacer 25mm x2</p>  |
| <p>10. VT-SIDE SCAN
VT-Sensor Brain (No Sensors)
VT-Sensor Display + Mixture
of x4 sensors</p>  | <p>11. VT646-AHD**
Rear-view Camera</p>  | |
| <p>12. VT-WARNING STICKER
BLIND SPOT
Vehicle Signage</p>  | <p>13. VT-C5M x3
5 Metre Cable</p>  | <p>14. VT-C15M
15 Metre Cable</p>  |

Product specifications can be found on the next page of this documents.

* additional charge may be involved.


**Not required for FORS but VisionTrack recommend.

t +44 (0) 1246 225 745
e info@visiontrack.com
w visiontrack.com
s support.visiontrack.com

VISIONTRACK

VisionTrack Copyright © 2020 - All Rights Reserved.

All manufacturers specifications are subject to change without notice. No liability will be accepted by VisionTrack for any errors or omissions in this information.



VT-FORS GOLD RIGID

VT5500-G

- Supports 4 channels AHD (1080P) +1 channel IPC (1080P)
- Supports hard disk for main recording
- Alarm integration for central monitoring
- Supports GPS, Wi-Fi and 3G/4G
- Built-in three-axis inertial sensor
- Vibration-resistant design



VT-LT ALERT

- Dual Voltage
- CE and EMC approved
- M.I.R.A. - tested for all on-and-off highway applications
- Epoxy sealed for greater durability against water
- Complete with anti-vibration gasket and mounting screws
- IOR approved - IOR-037568



VT-TIMER CUT OUT

- Six minute timer cut-out
- Auto Reset
- 12-14V
- IP67 rated - sealed against mud, water and vibration
- 30(H) x 88(W) x 47(D) mm



VT408-AHD

- DC 12V-24V
- 120°
- 62(L) x 44(H) x 62(W) (mm)
- -20°C + 70°C
- 1280 x 720 pixels



VT-SIDE SCAN

- 4 sensors mixed sensors (Flush/Non-Flush)
- PCB built into sensors
- Splash-proof ECU
- Digital distance display with buzzer
- DSM scanning technology
- Dual voltage



VT-WARNING STICKER BLIND SPOT



VT-C20-MINI

- 1/2.8" SONY 2.13-megapixel
- 1920 x 1080 resolution
- 0.05 Lux/F1.2 (Auto Gain on)
- 3.6mm
- DC 12V±10%
- 90(L) x 46(H) x 70(W)mm



VT-WNREVERSINGALARM

- Epoxy-sealed for greater durability
- Minimum 85 dB output
- M.I.R.A. tested for all on and off-road applications
- Pressure washable – IP67
- 2 Wire



VT-M4-7-AHD (Kit)

- 10.1-inch digital screen
- Resolution 1024 x 600p
- 4 video inputs and 4 trigger wires
- Power voltage of DC10V-36V
- 352(L) x 166(W) x 32(D) mm



VT408 Spacer 50mm

- 65(L) x 50(H) x 55(W) (mm)



VT408 Spacer 25mm

- 65(L) x 25(H) x 55(W) (mm)



VT646-AHD

- 1/3" colour lens
- 1280 x 720 resolution
- 120° wide-viewing angle)
- IR night vision
- 50(L) x 50(H) x 80(W)mm



For more information please go to
www.visiontrack.com



t +44 (0) 1246 225 745
e info@visiontrack.com
w visiontrack.com
s support.visiontrack.com



VisionTrack Copyright © 2020 - All Rights Reserved.
All manufacturers specifications are subject to change without notice. No liability will be accepted by VisionTrack for any errors or omissions in this information.